



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Diesel engines

Technical specifications	1.4 TDI/55 kW	1.4 TDI/66 kW	1.4 TDI/66 kW (A)	1.4 TDI/77 kW
Engine				
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front			
Cylinders	3			
Displacement [cm ³]	1422			
Bore x Stroke [mm x mm]	79.5 x 95.5			
Max. engine performance/revs [kW at rpm]	55/3000–3750	66/3000–3250		77/3500–3750
Max. torque/revs [Nm at rpm]	210/1500–2000	230/1750–2500		250/1750–2500
Compression ratio	16.2 : 1			
Emission limit	EU 6			
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system			
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	diesel			
Transmission				
Wheel drive	front wheel drive			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated		hydraulic single dry clutch disc with membrane spring, asbestos free
Transmission	manual 5-speed fully synchronized		automatic 7-speed, DSG, with Tiptronic manual gear changing	manual 5-speed fully synchronized
Transmission ratio	I-3.78 II-1.94 III-1.19 IV-0.82 V-0.63 R-3.60	I-3.78 II-1.94 III-1.19 IV-0.82 V-0.63 R-3.60	I-3.50 II-2.09 III-1.34 IV-0.93 V-0.97 VI-0.78 VII-0.65 R-3.72	I-3.78 II-1.94 III-1.19 IV-0.82 V-0.63 R-3.60
Axle ratio	3.389	3.389	4.438/3.227/4.176	3.389



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Diesel engines

Technical specifications		1.4 TDI/55 kW	1.4 TDI/66 kW	1.4 TDI/66 kW (A)	1.4 TDI/77 kW
Chassis					
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle		compound link crank-axle			
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system		hydraulic dual-diagonal circuit braking system vacuum assisted			
Brake – front		disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear		drum brakes			
Parking brake		manual, on rear wheels			
Steering system		direct rack and pinion steering with electro mechanic power steering			
Wheels		5Jx14"			6Jx15"
Tyres		175/70 R14			185/60 R15
Body					
Body		5 door, two compartment, 5 seater			
Drag coefficient c_w		0.302			0.306
Outside dimensions					
Length	[mm]	4257			
Width	[mm]	1732			
Height (at kerb weight)	[mm]	1467			
Wheel base	[mm]	2470			
Clearance (at kerb weight)	[mm]	135			
Height of the loading sill (at kerb weight)	[mm]	611			
Track front	[mm]	1463			1457
Track rear	[mm]	1457			1451
Inside dimensions					
Width of front seats	[mm]	1401			
Width of rear seats	[mm]	1386			
Headroom in front seats	[mm]	1021			
Headroom in rear seats	[mm]	967			
Storage capacity	[l]	530			
Storage capacity with rear seats folded down	[l]	1395			



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Diesel engines

Technical specifications		1.4 TDI/55 kW	1.4 TDI/66 kW	1.4 TDI/66 kW (A)	1.4 TDI/77 kW
Weights					
Kerb weight – incl. driver**	[kg]	1199	1199	1220	1208
Payload – incl. driver**	[kg]	530			
Total weight	[kg]	1654	1654	1675	1663
Max. roof load	[kg]	75			
Max. trailer load w/o brakes	[kg]	590	590	600	600
Max. trailer load with brakes – 12%	[kg]	1000	1100		
Max. trailer load with brakes – 8%	[kg]	1100	1200		
Max. nose weight	[kg]	50			
Liquids					
Tank capacity	[l]	45			
Performance/consumption					
Maximum speed	[km/h]	175	184	184	196
Acceleration 0–100 km/h	[s]	13.3	11.3	11.3	10.2
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	4.3	4.3	4.2	4.6
Consumption – extra-urban	[l/100 km]	3.6	3.6	3.5	3.9
Consumption – combined	[l/100 km]	3.8	3.8	3.8	4.1
CO ₂ emissions	[g/km]	102	102	103	110
Turning circle diameter	[m]	10.4			

The technical data is valid for the basic version.

** Figures apply to basic version, weight of driver 75 kg.



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Petrol engines

Technical specifications	1.0 MPI/55 kW	1.0 TSI/70 kW	1.0 TSI/81 kW	1.0 TSI/81 kW (A)
Engine				
Engine type	petrol engine, in-line, liquid cooling system, DOHC, transverse in front	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	3			
Displacement [cm ³]	999			
Bore x Stroke [mm x mm]	74.5 x 76.4			
Max. engine performance/revs [kW at rpm]	55/6200	70/5000–5500	81/5000–5500	
Max. torque/revs [Nm at rpm]	95/3000–4300	160/1500–3500	200/2000–3500	
Compression ratio	10.5 : 1			
Emission limit	EU 6			
Fuel injection system	electronic multipoint fuel injection MPI	electronically controlled direct injection		
Ignition	control unit controlled electronic ignition system			
Lubrication	force-feed lubrication with through-flow oil filter			
Fuel quality	unleaded petrol min. RON 95 (91)*	unleaded petrol min. RON 95		
Transmission				
Wheel drive	front wheel drive			
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free			two coaxial dry multiple-disk clutch, electro-hydraulically operated
Transmission	manual 5-speed fully synchronized		manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.64 II-1.95 III-1.27 IV-0.96 V-0.80 R-3.62	I-3.77 II-1.96 III-1.28 IV-0.93 V-0.74 R-3.18	I-3.77 II-1.96 III-1.28 IV-0.97 V-0.78 VI-0.64 R-3.18	I-3.77 II-2.27 III-1.53 IV-1.12 V-1.18 VI-0.95 VII-0.80 R-4.17
Axle ratio	4.812	3.625	3.625	4.438/3.227/4.176



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Petrol engines

Technical specifications		1.0 MPI/55 kW	1.0 TSI/70 kW	1.0 TSI/81 kW	1.0 TSI/81 kW (A)
Chassis					
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle		compound link crank-axle			
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system		hydraulic dual-diagonal circuit braking system vacuum assisted			
Brake – front		disc brakes with inner cooling, with single/piston floating caliper			
Brake – rear		drum brakes			disc brakes
Parking brake		manual, on rear wheels			
Steering system		direct rack and pinion steering with electro mechanic power steering			
Wheels		5Jx14"		6Jx15"	
Tyres		175/70 R14		185/60 R15	
Body					
Body		5 door, two compartment, 5 seater			
Drag coefficient c_w		0.304	0.308		0.310
Outside dimensions					
Length	[mm]	4257			
Width	[mm]	1732			
Height (at kerb weight)	[mm]	1467			
Wheel base	[mm]	2470			
Clearance (at kerb weight)	[mm]	135			
Height of the loading sill (at kerb weight)	[mm]	611			
Track front	[mm]	1463			1457
Track rear	[mm]	1457			1451
Inside dimensions					
Width of front seats	[mm]	1401			
Width of rear seats	[mm]	1386			
Headroom in front seats	[mm]	1021			
Headroom in rear seats	[mm]	967			
Storage capacity	[l]	530			
Storage capacity with rear seats folded down	[l]	1395			



ŠKODA
SIMPLY CLEVER

ŠKODA FABIA COMBI

Petrol engines

Technical specifications		1.0 MPI/55 kW	1.0 TSI/70 kW	1.0 TSI/81 kW	1.0 TSI/81 kW (A)
Weights					
Kerb weight – incl. driver**	[kg]	1104	1134	1154	1188
Payload – incl. driver**	[kg]	530			
Total weight	[kg]	1559	1589	1609	1643
Max. roof load	[kg]	75			
Max. trailer load w/o brakes	[kg]	550	560	570	590
Max. trailer load with brakes – 12%	[kg]	800	1000	1100	
Max. trailer load with brakes – 8%	[kg]	1000	1100		
Max. nose weight	[kg]	50			
Liquids					
Tank capacity	[l]	45			
Performance/consumption					
Maximum speed	[km/h]	175	187	199	199
Acceleration 0–100 km/h	[s]	14.9	10.8	9.6	9.9
Fuel consumption (1999/100/EC)					
Consumption – urban	[l/100 km]	5.8	5.1	5.3	5.4
Consumption – extra-urban	[l/100 km]	4.3	3.8	3.8	4.0
Consumption – combined	[l/100 km]	4.8	4.3	4.3	4.5
CO ₂ emissions	[g/km]	109	99	101	105
Turning circle diameter	[m]	10.4			

The technical data is valid for the basic version.

* Using low-octane fuel may affect engine performance.

** Figures apply to basic version, weight of driver 75 kg.