



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Petrol engines

Technical specifications	1.5 TSI/110 kW ACT	1.5 TSI/110 kW ACT (A)	2.0 TSI/206 kW 4x4 (A)
Engine			
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front		
Cylinders	4		
Displacement [cm ³]	1498		1984
Bore × Stroke [mm × mm]	74.5 × 85.9		82.5 × 92.8
Max. engine performance/revs [kW at rpm]	110/5000–6000		206/5000-6500
Max. torque/revs [Nm at rpm]	250/1500–3500		400/2000-4900
Compression ratio	10.5 : 1		9.3 : 1
Emission limit	EU 6 AP		
Fuel injection system	electronically controlled direct injection		electronically controlled combined (direct and port) injection
Ignition	control unit controlled electronic ignition system		
Lubrication	force-feed lubrication with through-flow oil filter		
Fuel quality	unleaded petrol min. RON 95		
Transmission			
Wheel drive	front wheel drive		four-wheel drive with automatic torque distribution
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro-hydraulically operated	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio	I-3.750 II-1.952 III-1.200 IV-0.925 V-0.767 VI-0.652 R-3.583	I-3.500 II-2.087 III-1.343 IV-0.933 V-0.974 VI-0.778 VII-0.653 R-3.722	I-3.400 II-2.750 III-1.767 IV-0.925 V-0.705 VI-0.755 VII-0.635 R-2.900
Axle ratio	3.944	I-4.800 II-3.429 III-4.500	I-4.813 II-3.667



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Petrol engines

Technical specifications	1.5 TSI/110 kW ACT	1.5 TSI/110 kW ACT (A)	2.0 TSI/206 kW 4x4 (A)
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted		
Brake – front	disc brakes with inner cooling, with single/piston floating caliper		
Brake – rear	disc brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Body			
Body	5 door, two compartment, 5 seater		
Drag coefficient c_w	0.314		
Outside dimensions			
Length [mm]	4862		
Width [mm]	1864		
Height (at kerb weight) [mm]	1477		1476
Wheel base (at kerb weight) [mm]	2841		
Clearance (at kerb weight) [mm]	150		136
Track front [mm]	1584		
Track rear [mm]	1572		
Inside dimensions			
Width of front seats [mm]	1507		
Width of rear seats [mm]	1519		
Headroom in front seats [mm]	1042		
Headroom in rear seats [mm]	1000		
Storage capacity [l]	660		
Storage capacity with rear seatback folded down [l]	1950		



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Petrol engines

Technical specifications		1.5 TSI/110 kW ACT	1.5 TSI/110 kW ACT (A)	2.0 TSI/206 kW 4x4 (A)
Weights				
Kerb weight – incl. driver*	[kg]	1482–1690	1492–1700	1670–1878
Payload – incl. driver*	[kg]	434–642	504–712	515–723
Total weight	[kg]	2049	2129	2318
Max. roof load	[kg]	100		
Max. trailer load w/o brakes	[kg]	740		750
Max. trailer load with brakes – 12%	[kg]	1600		2200
Max. trailer load with brakes – 8%	[kg]	1900		2200
Max. nose weight	[kg]	90		
Liquids				
Tank capacity	[l]	66		
Performance/consumption				
Maximum speed	[km/h]	213	212	250
Acceleration 0–100 km/h	[s]	9.2	9.3	5.3
Fuel consumption (NEDC)				
– urban	[l/100 km]	6.6–6.8	6.7–6.8	9.7
– extra-urban	[l/100 km]	4.4–4.6	4.6–4.8	5.9–6.1
– combined	[l/100 km]	5.2–5.4	5.3–5.6	7.3–7.4
CO ₂ emissions	[g/km]	120–125	122–128	167–169
Fuel consumption (WLTP)				
– combined	[l/100 km]	–	–	–
CO ₂ emissions	[g/km]	–	–	–
Turning circle diameter	[m]	11.1		

The technical data is valid for the basic version.

* Figures apply to basic version, weight of driver 75 kg.

– The technical data are not available on the press deadline.

The specified fuel consumption and emission data have been determined according to the measurement procedures prescribed by law. Since 1st September 2017, certain new vehicles are already being type-approved according to the Worldwide Harmonized Light Vehicles Test Procedure (WLTP), a more realistic test procedure for measuring fuel consumption and CO₂ emissions. Starting on September 1st 2018,



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Petrol engines

the New European Driving Cycle (NEDC) will be replaced by the WLTP in stages. Owing to the more realistic test conditions, the fuel consumption and CO₂ emissions measured according to the WLTP will, in many cases, be higher than those measured according to the NEDC.


We are currently still required by law to state the NEDC figures. In the case of new vehicles which have been type-approved according to the WLTP, the NEDC figures are derived from the WLTP data. It is possible to specify the WLTP figures voluntarily in addition until such time as this is required by law. In cases where the NEDC figures are specified as value ranges, these do not refer to a particular individual vehicle and do not constitute part of the sales offering. They are intended exclusively as a means of comparison between different vehicle types. Additional equipment and accessories (e.g. add-on parts, different tyre formats, etc.) may change the relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, in conjunction with weather and traffic conditions and individual driving style, may affect fuel consumption, electrical power consumption, CO₂ emissions and the performance figures for the vehicle.



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Petrol engines





ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Diesel engines

Technical specifications	2.0 TDI/90 kW (A)	2.0 TDI/110 kW	2.0 TDI/110 kW (A)	2.0 TDI/147 kW (A)	2.0 TDI/147 kW 4×4 (A)
Engine					
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front				
Cylinders	4				
Displacement [cm ³]	1968				
Bore × Stroke [mm × mm]	81.0 × 95.5				
Max. engine performance/revs [kW at rpm]	90/3500–4250	110/3250–4200	110/3000–4200	147/3600–4100	
Max. torque/revs [Nm at rpm]	250/1500–3250	340/1600–3000	360/1600–2750	400/1750–3500	
Compression ratio	16.0 : 1			15.5 : 1	
Emission limit	EU 6 AP				
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system				
Lubrication	force-feed lubrication with through-flow oil filter				
Fuel quality	diesel				
Transmission					
Wheel drive	front wheel drive				four-wheel drive with automatic torque distribution
Clutch	two coaxial dry multiple-disk clutch, electro-hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial wet multiple-disk clutch, electro-hydraulically operated		
Transmission	automatic 7-speed, DSG, with Tiptronic manual gear changing	manual 6-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing		
Transmission ratio	I-3.500 II-2.087 III-1.343 IV-0.933 V-0.974 VI-0.778 VII-0,653 R-3.722	I-3.769 II-1.958 III-1.257 IV-0.870 V-0.857 VI-0.717 R-4.549	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900
Axle ratio	I-4.800 II-3.429 III-4.500	I-3.684 II-2.917	I-4.471 II-3.304	I-4.471 II-3.304	I-4.471 II-3.304



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Diesel engines

Technical specifications	2.0 TDI/90 kW (A)	2.0 TDI/110 kW	2.0 TDI/110 kW (A)	2.0 TDI/147 kW (A)	2.0 TDI/147 kW 4x4 (A)
Chassis					
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser				
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser				
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs				
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted				
Brake – front	disc brakes with inner cooling, with single/piston floating caliper				
Brake – rear	disc brakes				
Parking brake	electromechanical, on rear wheels				
Steering system	direct rack and pinion steering with electro mechanic power steering				
Body					
Body	5 door, two compartment, 5 seater				
Drag coefficient c_w	0.304	0.301	0.301	0.304	0.308
Outside dimensions					
Length [mm]	4862				
Width [mm]	1864				
Height (at kerb weight) [mm]	1477				1476
Wheel base (at kerb weight) [mm]	2841				
Clearance (at kerb weight) [mm]	147	139			136
Track front [mm]	1584				
Track rear [mm]	1572				
Inside dimensions					
Width of front seats [mm]	1507				
Width of rear seats [mm]	1519				
Headroom in front seats [mm]	1042				
Headroom in rear seats [mm]	1000				
Storage capacity [l]	660				
Storage capacity with rear seatback folded down [l]	1950				



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Diesel engines

Technical specifications		2.0 TDI/90 kW (A)	2.0 TDI/110 kW	2.0 TDI/110 kW (A)	2.0 TDI/147 kW (A)	2.0 TDI/147 kW 4x4 (A)
Weights						
Kerb weight – incl. driver*	[kg]	1574–1782	1577–1785	1607–1815	1598–1806	1674–1882
Payload – incl. driver*	[kg]	495–703	503–711	492–700	506–714	473–681
Total weight	[kg]	2202	2213	2232	2237	2280
Max. roof load	[kg]			100		
Max. trailer load w/o brakes	[kg]			750		
Max. trailer load with brakes – 12%	[kg]	1500		2000		2200
Max. trailer load with brakes – 8%	[kg]	1800		2000		2200
Max. nose weight	[kg]			90		
Liquids						
Tank capacity	[l]			66		
Performance/consumption						
Maximum speed	[km/h]	200	215	213	234	229
Acceleration 0–100 km/h	[s]	11.1	9.2	9.2	7.9	7.3
Fuel consumption (NEDC)						
– urban	[l/100 km]	5.1–5.2	5.5–5.7	4.9–5.0	6.0	6.3–6.4
– extra-urban	[l/100 km]	3.6–3.8	3.6–3.8	3.5–3.6	3.9–4.0	4.3–4.4
– combined	[l/100 km]	4.1–4.3	4.3–4.5	4.0–4.2	4.6–4.7	5.0–5.1
CO ₂ emissions	[g/km]	110–116	114–118	106–109	122–124	132–135
Fuel consumption (WLTP)						
– combined	[l/100 km]	–	–	–	–	–
CO ₂ emissions	[g/km]	–	–	–	–	–
Turning circle diameter	[m]			11.1		

The technical data is valid for the basic version.

* Figures apply to basic version, weight of driver 75 kg.

– The technical data are not available on the press deadline.

The specified fuel consumption and emission data have been determined according to the measurement procedures prescribed by law. Since 1st September 2017, certain new vehicles are already being type-approved according to the Worldwide Harmonized Light Vehicles Test Procedure (WLTP), a more realistic test procedure for measuring fuel consumption and CO₂ emissions. Starting on September 1st 2018,



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Diesel engines

the New European Driving Cycle (NEDC) will be replaced by the WLTP in stages. Owing to the more realistic test conditions, the fuel consumption and CO₂ emissions measured according to the WLTP will, in many cases, be higher than those measured according to the NEDC.

We are currently still required by law to state the NEDC figures. In the case of new vehicles which have been type-approved according to the WLTP, the NEDC figures are derived from the WLTP data. It is possible to specify the WLTP figures voluntarily in addition until such time as this is required by law. In cases where the NEDC figures are specified as value ranges, these do not refer to a particular individual vehicle and do not constitute part of the sales offering. They are intended exclusively as a means of comparison between different vehicle types. Additional equipment and accessories (e.g. add-on parts, different tyre formats, etc.) may change the relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, in conjunction with weather and traffic conditions and individual driving style, may affect fuel consumption, electrical power consumption, CO₂ emissions and the performance figures for the vehicle.



ŠKODA
SIMPLY CLEVER

ŠKODA SUPERB COMBI

Diesel engines

