

Enyaq Coupé

Technical specifications	Enyaq Coupé 60	Enyaq Coupé 85	Enyaq Coupé 85x	Enyaq Coupé RS
Engine				
Engine type	permanent magnet synchronous motor		rear – permanent magnet synchronous motor / front – asynchronous motor	
Max. system engine performance [kW]	140*	210*	220*	250*
Battery capacity gross (net) [kWh]	61 (58)	82 (77)		
Battery type	LFP (DC-high-voltage)	NMC (DC-high-voltage)		
Transmission				
Wheel drive	rear wheel drive		four-wheel drive	
Chassis				
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle	multi-element axle, with five transverse links and torsion stabiliser			
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted			
Brake – front	disc brakes with inner cooling, with single-piston floating caliper	disc brakes with inner cooling, with two-piston floating caliper		
Brake – rear	drum brakes			
Parking brake	electromechanical, on rear wheels			
Steering system	direct rack and pinion steering with electro mechanic power steering			electromechanical power steering with variable ratio
Body				
Body	5 door, two compartment, 5 seater			
Drag coefficient c _d	0.231–0.258	0.229–0.256		0.238–0.252
Outside dimensions				
Length [mm]	4658			4660
Width [mm]	1879			
Height (at kerb weight) [mm]	1623	1621		1608
Wheel base [mm]	2766			2769
Clearance (at kerb weight) [mm]	183	181		167
Height of the loading sill (at kerb weight) [mm]	795	792		779
Track front [mm]	1587			1589
Track rear [mm]	1561			1568

Enyaq Coupé

Technical specifications		Enyaq Coupé 60	Enyaq Coupé 85	Enyaq Coupé 85x	Enyaq Coupé RS
Inside dimensions					
Width of front seats	[mm]			1506	
Width of rear seats	[mm]			1488	
Headroom in front seats	[mm]			1095	
Headroom in rear seats	[mm]			990	
Storage capacity	[l]			570	
Storage capacity – with rear seatback folded down	[l]			1610	
Weights					
Kerb weight – incl. driver 75 kg	[kg]	2070–2179	2155–2267	2223–2335	2243–2353
Payload – incl. driver 75 kg	[kg]	496–605	458–570	490–602	472–582
Total weight	[kg]	2600	2650	2750	2750
Max. roof load	[kg]			75	
Max. trailer load w/o brakes	[kg]			750	
Max. trailer load with brakes – 12%	[kg]	1000	2000		2200
Max. trailer load with brakes – 8%	[kg]	1200	2000		2200
Max. nose weight	[kg]		88		
Performance/consumption					
Maximum speed	[km/h]	160		180	
Acceleration 0–100 km/h	[s]	8.6	6.6	6.3	5.4
Fuel consumption	[kWh/100 km]	14.7-15.6	14.8-15.8	15.0-16.0	15.6-17.1
CO ₂ emissions	[g/km]			0	
Range (WLTP)	[km]	439-463	561-593	561-593	528-572
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/6 h 30 min		11 kW/8 h 30 min	
DC charging (10–80 %) – power/time		105 kW/26 min		165 kW/29 min	
Turning circle diameter	[m]		9.3		10.8

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.

* The maximum power is determined in accordance with UN-GTR.21. The maximum power is available when the high-voltage battery is at its highest possible state of charge (SoC) and operating within its optimal temperature range. The power available varies according to the driving scenario and is influenced by factors including the battery's temperature, its SoC, and the physical ageing of the high-voltage battery.

Enyaq Coupé

