

Enyaq iV



Technical specifications		ENYAQ iV 50	ENYAQ iV 60	ENYAQ iV 80	ENYAQ iV 80x
Engine					
Engine type		permanent magnet synchronous motor			rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance	[kW]	109*	132*	150*	195**
Max. torque	[Nm]	220	310		425
Battery capacity brutto (netto)	[kWh]	55 (52)	62 (58)	82 (77)	
Battery type		Li-Ion (DC-high-voltage)			
Transmission					
Wheel drive		rear wheel drive			four-wheel drive
Transmission		single-speed			two single-speed
Axle ratio		4.389			rear – 3.900 / front – 2.760
Chassis					
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle		multi-element axle, with five transverse links and torsion stabiliser			
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted			
Brake – front		disc brakes with inner cooling, with single-piston floating caliper			disc brakes with inner cooling, with two-piston floating caliper
Brake – rear		drum brakes			
Parking brake		electromechanical, on rear wheels			
Steering system		direct rack and pinion steering with electro mechanic power steering			
Body					
Body		5 door, two compartment, 5 seater			
Drag coefficient c _w		0.262–0.272	0.255–0.277	0.258–0.280	

Enyaq iV



Technical specifications		ENYAQ iV 50		ENYAQ iV 60		ENYAQ iV 80		ENYAQ iV 80x	
Outside dimensions									
Length	[mm]	4649							
Width	[mm]	1879							
Height (at kerb weight)	[mm]	1619		1621		1620			
Wheel base	[mm]	2764				2765			
Clearance (at kerb weight)	[mm]	186		188		187			
Height of the loading sill (at kerb weight)	[mm]	704		705		704			
Track front	[mm]	1587							
Track rear	[mm]	1565							
Inside dimensions									
Width of front seats	[mm]	1506							
Width of rear seats	[mm]	1488							
Headroom in front seats	[mm]	1056							
Headroom in rear seats	[mm]	990							
Storage capacity	[l]	585							
Storage capacity – with rear seatback folded down	[l]	1710							
Weights									
Kerb weight – incl. driver 75 kg	[kg]	1941–2055		1999–2174		2111–2252		2193–2381	
Payload – incl. driver 75 kg	[kg]	430–544		401–576		423–564		440–628	
Total weight	[kg]	2410		2500		2600		2746	
Max. roof load	[kg]	75							
Max. trailer load w/o brakes	[kg]	–		750					
Max. trailer load with brakes – 12%	[kg]	–		1000				1200	
Max. trailer load with brakes – 8%	[kg]	–		1200				1400	
Max. nose weight	[kg]	–		75					

Enyaq iV



Technical specifications	ENYAQ iV 50	ENYAQ iV 60	ENYAQ iV 80	ENYAQ iV 80x
Performance/consumption				
Maximum speed [km/h]	160			
Acceleration 0–100 km/h [s]	11.1	8.7	8.5	6.8
Fuel consumption – combined (WLTP) [kWh/100 km]	15.7–16.2	15.8–17.0	15.6–17.0	16.5–17.8
CO ₂ emissions [g/km]	0			
Range (WLTP) [km]	370	399	548	524
AC charging (0–100 %) – power/time (according to the type of cable)	7.2 kW/7 h 30 min	11 kW/6 h 15 min	11 kW/7 h 30 min	11 kW/7 h 30 min
DC charging (10–80 %) – power/time	110 kW/36 min	120 kW/35 min	135 kW/29 min	135 kW/36 min
Turning circle diameter [m]	9.3			10.8

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.


* The availability of the maximum electrical output could be limited. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery.

** Maximum electrical output of 195 kW: Maximum output that can be accessed for a maximum of 30 seconds, calculated in accordance with UN GTR No. 21. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery. The availability of the maximum power requires the high-voltage battery to be between 23°C and 50°C and have a charge level of > 88%. Deviations from the aforementioned parameters in particular may lead to a reduction in power, through to the complete unavailability of the maximum power.

The battery temperature can be indirectly influenced by the auxiliary air conditioner to a certain extent and the charge level can, for example, be adjusted in the vehicle. The amount of power available at a particular time is shown in the vehicle's power display. To maintain the high-voltage battery's usable capacity as effectively as possible, a battery charging target of 80% is recommended if the vehicle is used daily (to be switched to 100% prior to long-distance journeys, for example).

Enyaq iV

SKODA



Enyaq RS iV



Technical specifications		80x RS
Engine		
Engine type		rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance	[kW]	220*
Max. torque	[Nm]	460
Battery capacity brutto (netto)	[kWh]	82 (77)
Battery type		Li-Ion (DC-high-voltage)
Transmission		
Wheel drive		four-wheel drive
Transmission		two single-speed
Axle ratio		rear – 3.900 / front – 2.760
Chassis		
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser
Rear axle		multi-element axle, with five transverse links and torsion stabiliser
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted
Brake – front		disc brakes with inner cooling, with two-piston floating caliper
Brake – rear		drum brakes
Parking brake		electromechanical, on rear wheels
Steering system		electromechanical power steering with variable ratio
Body		
Body		5 door, two compartment, 5 seater
Drag coefficient C_w		0.265–0.277
Outside dimensions		
Length	[mm]	4653
Width	[mm]	1879
Height (at kerb weight)	[mm]	1605
Wheel base	[mm]	2768
Clearance (at kerb weight)	[mm]	173
Height of the loading sill (at kerb weight)	[mm]	688
Track front	[mm]	1589
Track rear	[mm]	1573

Enyaq RS iV




Technical specifications		80x RS
Inside dimensions		
Width of front seats	[mm]	1506
Width of rear seats	[mm]	1488
Headroom in front seats	[mm]	1056
Headroom in rear seats	[mm]	990
Storage capacity	[l]	585
Storage capacity – with rear seatback folded down	[l]	1710
Weights		
Kerb weight – incl. driver 75 kg	[kg]	2258–2394
Payload – incl. driver 75 kg	[kg]	431–567
Total weight	[kg]	2750
Max. roof load	[kg]	75
Max. trailer load w/o brakes	[kg]	750
Max. trailer load with brakes – 12%	[kg]	1200
Max. trailer load with brakes – 8%	[kg]	1400
Max. nose weight	[kg]	75
Performance/consumption		
Maximum speed	[km/h]	180
Acceleration 0–100 km/h	[s]	6.5
Fuel consumption – combined (WLTP)	[kWh/100 km]	16.9–17.8
CO ₂ emissions	[g/km]	0
Range (WLTP)	[km]	517
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/7 h 30 min
DC charging (10–80 %) – power/time		135 kW/36 min
Turning circle diameter	[m]	10.8

* Maximum electrical output of 220 kW: Maximum output that can be accessed for a maximum of 30 seconds, calculated in accordance with UN GTR No. 21. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery. The availability of the maximum power requires the high-voltage battery to be between 23°C and 50°C and have a charge level of > 88%. Deviations from the aforementioned parameters in particular may lead to a reduction in power, through to the complete unavailability of the maximum power.

The battery temperature can be indirectly influenced by the auxiliary air conditioner to a certain extent and the charge level can, for example, be adjusted in the vehicle. The amount of power available at a particular time is shown in the vehicle's power display. To maintain the high-voltage battery's usable capacity as effectively as possible, a battery charging target of 80% is recommended if the vehicle is used daily (to be switched to 100% prior to long-distance journeys, for example).

Enyaq RS iV

SKODA



Enyaq Coupé iV



Technical specifications	60	80	80x
Engine			
Engine type	permanent magnet synchronous motor		rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance [kW]	132*	150*	195**
Max. torque [Nm]	310		425
Battery capacity brutto (netto) [kWh]	62 (58)	82 (77)	82 (77)
Battery type	Li-Ion (DC-high-voltage)		
Transmission			
Wheel drive	rear wheel drive		four-wheel drive
Transmission	single-speed		two single-speed
Axle ratio	4.389		rear – 3.900 / front – 2.760
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with five transverse links and torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted		
Brake – front	disc brakes with inner cooling, with single-piston floating caliper		disc brakes with inner cooling, with two-piston floating caliper
Brake – rear	drum brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Body			
Body	5 door, two compartment, 5 seater		
Drag coefficient c _w	0.234–0.263	0.240–0.271	

Enyaq Coupé iV



Technical specifications		60		80		80x		
Outside dimensions								
Length	[mm]	4653						
Width	[mm]	1879						
Height (at kerb weight)	[mm]	1621						
Wheel base	[mm]	2765						
Clearance (at kerb weight)	[mm]	193						
Height of the loading sill (at kerb weight)	[mm]	792			793			
Track front	[mm]	1587						
Track rear	[mm]	1565						
Inside dimensions								
Width of front seats	[mm]	1506						
Width of rear seats	[mm]	1488						
Headroom in front seats	[mm]	1095						
Headroom in rear seats	[mm]	990						
Storage capacity	[l]	570						
Storage capacity – with rear seatback folded down	[l]	1610						
Weights								
Kerb weight – incl. driver 75 kg	[kg]	2008–2154			2119–2250		2214–2359	
Payload – incl. driver 75 kg	[kg]	431–577			425–556		466–611	
Total weight	[kg]	2510			2600		2750	
Max. roof load	[kg]	75						
Max. trailer load w/o brakes	[kg]	750						
Max. trailer load with brakes – 12%	[kg]	1000				1200		
Max. trailer load with brakes – 8%	[kg]	1200				1400		
Max. nose weight	[kg]	75						

Enyaq Coupé iV



Technical specifications	60	80	80x
Performance/consumption			
Maximum speed [km/h]	160		
Acceleration 0–100 km/h [s]	8.7	8.5	6.8
Fuel consumption – combined (WLTP) [kWh/100 km]	15.4–16.7	15.2–16.6	16.2–17.4
CO ₂ emissions [g/km]	0		
Range (WLTP) [km]	408	560	534
AC charging (0–100 %) – power/time (according to the type of cable)	11 kW/6 h 15 min	11 kW/7 h 30 min	11 kW/7 h 30 min
DC charging (10–80 %) – power/time	120 kW/35 min	135 kW/29 min	135 kW/36 min
Turning circle diameter [m]	9.3		10.8

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.


* The availability of the maximum electrical output could be limited. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery.

** Maximum electrical output of 195 kW: Maximum output that can be accessed for a maximum of 30 seconds, calculated in accordance with UN GTR No. 21. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery. The availability of the maximum power requires the high-voltage battery to be between 23°C and 50°C and have a charge level of > 88%. Deviations from the aforementioned parameters in particular may lead to a reduction in power, through to the complete unavailability of the maximum power.

The battery temperature can be indirectly influenced by the auxiliary air conditioner to a certain extent and the charge level can, for example, be adjusted in the vehicle. The amount of power available at a particular time is shown in the vehicle's power display. To maintain the high-voltage battery's usable capacity as effectively as possible, a battery charging target of 80% is recommended if the vehicle is used daily (to be switched to 100% prior to long-distance journeys, for example).

Enyaq Coupé iV

SKODA



Enyaq Coupé RS iV



Technical specifications		80x RS
Engine		
Engine type		rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance	[kW]	220*
Max. torque	[Nm]	460
Battery capacity brutto (netto)	[kWh]	82 (77)
Battery type		Li-Ion (DC-high-voltage)
Transmission		
Wheel drive		four-wheel drive
Transmission		two single-speed
Axle ratio		rear – 3.900 / front – 2.760
Chassis		
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser
Rear axle		multi-element axle, with five transverse links and torsion stabiliser
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted
Brake – front		disc brakes with inner cooling, with two-piston floating caliper
Brake – rear		drum brakes
Parking brake		electromechanical, on rear wheels
Steering system		electromechanical power steering with variable ratio
Body		
Body		5 door, two compartment, 5 seater
Drag coefficient C_w		0.248–0.272
Outside dimensions		
Length	[mm]	4653
Width	[mm]	1879
Height (at kerb weight)	[mm]	1608
Wheel base	[mm]	2768
Clearance (at kerb weight)	[mm]	181
Height of the loading sill (at kerb weight)	[mm]	779
Track front	[mm]	1589
Track rear	[mm]	1573

Enyaq Coupé RS iV



Technical specifications		80x RS
Inside dimensions		
Width of front seats	[mm]	1506
Width of rear seats	[mm]	1488
Headroom in front seats	[mm]	1095
Headroom in rear seats	[mm]	990
Storage capacity	[l]	570
Storage capacity – with rear seatback folded down	[l]	1610
Weights		
Kerb weight – incl. driver 75 kg	[kg]	2264–2374
Payload – incl. driver 75 kg	[kg]	451–561
Total weight	[kg]	2750
Max. roof load	[kg]	75
Max. trailer load w/o brakes	[kg]	750
Max. trailer load with brakes – 12%	[kg]	1200
Max. trailer load with brakes – 8%	[kg]	1400
Max. nose weight	[kg]	75
Performance/consumption		
Maximum speed	[km/h]	180
Acceleration 0–100 km/h	[s]	6.5
Fuel consumption – combined (WLTP)	[kWh/100 km]	16.7–17.5
CO ₂ emissions	[g/km]	0
Range (WLTP)	[km]	523
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/7 h 30 min
DC charging (10–80 %) – power/time		135 kW/36 min
Turning circle diameter	[m]	10.8

* Maximum electrical output of 220 kW: Maximum output that can be accessed for a maximum of 30 seconds, calculated in accordance with UN GTR No. 21. The amount of power available in individual driving situations depends on various factors, such as ambient temperature and the charge status, temperature, and condition or physical age of the high-voltage battery. The availability of the maximum power requires the high-voltage battery to be between 23°C and 50°C and have a charge level of > 88%. Deviations from the aforementioned parameters in particular may lead to a reduction in power, through to the complete unavailability of the maximum power.

The battery temperature can be indirectly influenced by the auxiliary air conditioner to a certain extent and the charge level can, for example, be adjusted in the vehicle. The amount of power available at a particular time is shown in the vehicle's power display. To maintain the high-voltage battery's usable capacity as effectively as possible, a battery charging target of 80% is recommended if the vehicle is used daily (to be switched to 100% prior to long-distance journeys, for example).

Enyaq Coupé RS iV

SKODA

