

Technical specifications		Elroq 50	Elroq 60	Elroq 85	Elroq RS
Engine					
Engine type		permanent magnet synchronous motor			rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance	[kW]	125*	150*	210*	250*
Battery capacity gross (net)	[kWh]	55 (52)	63 (59)	82 (77)	84 (79)
Battery type		Li-Ion (DC-high-voltage)			
Transmission					
Wheel drive		rear wheel drive			four-wheel drive
Transmission		single-speed			two single-speed
Axle ratio		4.389		3.895	rear – 3.895 / front – 3.783
Chassis					
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle		multi-element axle, with five transverse links and torsion stabiliser			
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted			
Brake – front		disc brakes with inner cooling, with single-piston floating caliper		disc brakes with inner cooling, with two-piston floating caliper	
Brake – rear		drum brakes			
Parking brake		electromechanical, on rear wheels			
Steering system		direct rack and pinion steering with electro mechanic power steering			electromechanical power steering with variable ratio
Body					
Body		5 door, two compartment, 5 seater			
Drag coefficient c _d		0.264–0.277		0.261–0.277	0.267–0.276
Outside dimensions					
Length	[mm]	4488			
Width	[mm]	1884			
Height (at kerb weight)	[mm]	1625			1608
Wheel base	[mm]	2765			2769
Clearance (at kerb weight)	[mm]	186			170
Height of the loading sill (at kerb weight)	[mm]	702			684
Track front	[mm]	1587			1589
Track rear	[mm]	1562			1569

Technical specifications		Elroq 50	Elroq 60	Elroq 85	Elroq RS
Inside dimensions					
Width of front seats	[mm]	1506			
Width of rear seats	[mm]	1488			
Headroom in front seats	[mm]	1056			
Headroom in rear seats	[mm]	990			
Storage capacity	[l]	470			
Storage capacity – with rear seatback folded down	[l]	1580			
Weights					
Kerb weight – incl. driver 75 kg	[kg]	1949–2089	1978–2115	2119–2256	2229–2342
Payload – incl. driver 75 kg	[kg]	413–553	417–554	469–606	469–582
Total weight	[kg]	2427	2457	2650	2736
Max. roof load	[kg]	75			
Max. trailer load w/o brakes	[kg]	750			
Max. trailer load with brakes – 12%	[kg]	1000			1200
Max. trailer load with brakes – 8%	[kg]	1200			1400
Max. nose weight	[kg]	75			
Performance/consumption					
Maximum speed	[km/h]	160	160	180	180
Acceleration 0–100 km/h	[s]	9.0	8.0	6.6	5.4
Fuel consumption – combined (WLTP)	[kWh/100 km]	15.7	15.7	15.2	16.2
CO ₂ emissions	[g/km]	0			
Range (WLTP)	[km]	377	430	574**	549
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/5 h 30 min	11 kW/6 h 30 min	11 kW/8 h 00 min	11 kW/8 h 30 min
DC charging (10–80 %) – power/time		145 kW/25 min	165 kW/24 min	135 kW/28 min**	185 kW/26 min
Turning circle diameter	[m]	9.3			10.8

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.

* The maximum power is determined in accordance with UN-GTR.21. The maximum power is available when the high-voltage battery is at its highest possible state of charge (SoC) and operating within its optimal temperature range. The power available varies according to the driving scenario and is influenced by factors including the battery's temperature, its SoC, and the physical ageing of the high-voltage battery.

** Values valid for cars manufactured from June 2025.

Elroq

SKODA

