

Technical specifications		Peaq 60	Peaq 90	Peaq 90x
Engine				
Engine type		permanent magnet synchronous motor		rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance	[kW]	150*	210*	220*
Battery capacity gross (net)	[kWh]	63 (59)	91 (86)	
Battery type		NMC (DC-high-voltage)		
Transmission				
Wheel drive		rear wheel drive		four-wheel drive
Chassis				
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle		multi-element axle, with five transverse links and torsion stabiliser		
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted		
Brake – front		disc brakes with inner cooling, with two-piston floating caliper		
Brake – rear		drum brakes		
Parking brake		electromechanical, on rear wheels		
Steering system		direct rack and pinion steering with electro mechanic power steering		
Body				
Body		5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c _d		0.249–0.265		0.250–0.267
Outside dimensions				
Length	[mm]	4874		
Width	[mm]	1867		
Height (at kerb weight)	[mm]	1664		
Wheel base	[mm]	2965		
Clearance (at kerb weight)	[mm]	184 {183}		
Height of the loading sill (at kerb weight)	[mm]	761 {760}		
Track front	[mm]	1587		
Track rear	[mm]	1555 {1557}		

Peaq



Technical specifications		Peaq 60	Peaq 90	Peaq 90x
Inside dimensions				
Width of front seats	[mm]	1510		
Width of rear seats (2 nd /3 rd row)	[mm]	1506/– {1506/1286}		
Headroom in front seats	[mm]	1069		
Headroom in rear seats (2 nd /3 rd row)	[mm]	1011/– {1011/961}		
Storage capacity (behind 3 rd row of seats up to headrests)	[l]	{299}		
Storage capacity up to the rear shelf {with 3 rd row of seats folded down}	[l]	935 {890}		
Storage capacity – with rear seatback folded down	[l]	2150 {2075}		
Front storage capacity	[l]	37		
Weights				
Kerb weight – incl. driver 75 kg	[kg]	2125–2253 {2156–2279}	2309–2432 {2334–2449}	2382–2504 {2407–2529}
Payload – incl. driver 75 kg	[kg]	479–607 {538–639}	473–596 {535–650}	387–509 {536–658}
Total weight	[kg]	2657 {2700–2752}	2830 {2909}	2816 {2990}
Max. roof load	[kg]	75		
Max. trailer load w/o brakes	[kg]	750		
Max. trailer load with brakes – 12%	[kg]	1800	2000	
Max. trailer load with brakes – 8%	[kg]	1800	2000	
Max. nose weight	[kg]	72	80	
Performance/consumption				
Maximum speed	[km/h]	160	180	
Acceleration 0–100 km/h	[s]	8.4 {8.5}	7.1	6.7 {6.8}
Fuel consumption – combined (WLTP)	[kWh/100 km]	14.7	15.0	15.8
CO ₂ emissions	[g/km]	0		
Range (WLTP)	[km]	459	647	613
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/6 h 30 min	11 kW/9 h	
DC charging (10–80 %) – power/time		160 kW/27 min	199 kW/28 min	
Turning circle diameter	[m]	9.9		11.4

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.

{ } Applies to 7-seater.

* The maximum power is determined in accordance with UN-GTR.21. The maximum power is available when the high-voltage battery is at its highest possible state of charge (SoC) and operating within its optimal temperature range. The power available varies according to the driving scenario and is influenced by factors including the battery's temperature, its SoC, and the physical ageing of the high-voltage battery.

Peaq

SKODA

