

Technical specifications	Peaq 60	Peaq 90	Peaq 90x
Engine			
Engine type	permanent magnet synchronous motor		rear – permanent magnet synchronous motor / front – asynchronous motor
Max. system engine performance [kW]	150*	210*	220*
Battery capacity gross (net) [kWh]	63 (59)	91 (86)	
Battery type	NMC (DC-high-voltage)		
Transmission			
Wheel drive	rear wheel drive		four-wheel drive
Chassis			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser		
Rear axle	multi-element axle, with five transverse links and torsion stabiliser		
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs		
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted		
Brake – front	disc brakes with inner cooling, with two-piston floating caliper		
Brake – rear	drum brakes		
Parking brake	electromechanical, on rear wheels		
Steering system	direct rack and pinion steering with electro mechanic power steering		
Body			
Body	5 door, two compartment, 5 seater {7 seater}		
Drag coefficient c _d	0.249–0.265		0.250–0.267
Outside dimensions			
Length [mm]	4874		
Width [mm]	1867		
Height (at kerb weight) [mm]	1664		
Wheel base [mm]	2965		
Clearance (at kerb weight) [mm]	184 {183}		
Height of the loading sill (at kerb weight) [mm]	761 {760}		
Track front [mm]	1587		
Track rear [mm]	1555 {1557}		

Peaq



Technical specifications		Peaq 60		Peaq 90		Peaq 90x	
Inside dimensions							
Width of front seats	[mm]	1510					
Width of rear seats (2 nd /3 rd row)	[mm]	1506/– {1506/1286}					
Headroom in front seats	[mm]	1069					
Headroom in rear seats (2 nd /3 rd row)	[mm]	1011/– {1011/961}					
Storage capacity (behind 3 rd row of seats up to headrests)	[l]	{299}					
Storage capacity up to the rear shelf {with 3 rd row of seats folded down}	[l]	935 {890}					
Storage capacity – with rear seatback folded down	[l]	2150 {2075}					
Front storage capacity	[l]	37					
Weights							
Kerb weight – incl. driver 75 kg	[kg]	2125–2253 {2156–2279}		2309–2432 {2334–2449}		2382–2504 {2407–2529}	
Payload – incl. driver 75 kg	[kg]	479–607 {538–639}		473–596 {535–650}		387–509 {536–658}	
Total weight	[kg]	2657 {2700–2752}		2830 {2909}		2816 {2990}	
Max. roof load	[kg]	75					
Max. trailer load w/o brakes	[kg]	750					
Max. trailer load with brakes – 12%	[kg]	1800				2000	
Max. trailer load with brakes – 8%	[kg]	1800				2000	
Max. nose weight	[kg]	72				80	
Performance/consumption							
Maximum speed	[km/h]	160		180			
Acceleration 0–100 km/h	[s]	8.4 {8.5}		7.1		6.7 {6.8}	
Fuel consumption – combined (WLTP)	[kWh/100 km]	14.7		15.0		15.8	
CO ₂ emissions	[g/km]	0					
Range (WLTP)	[km]	459		647		613	
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/6 h 30 min		11 kW/9 h			
DC charging (10–80 %) – power/time		160 kW/27 min		199 kW/28 min			
Turning circle diameter	[m]	9.9				11.4	

Technical specifications do not apply for Sportline cars. Specifications may also differ depending on the battery version and chassis configuration.

{ } Applies to 7-seater.

* The maximum power is determined in accordance with UN-GTR.21. The maximum power is available when the high-voltage battery is at its highest possible state of charge (SoC) and operating within its optimal temperature range. The power available varies according to the driving scenario and is influenced by factors including the battery's temperature, its SoC, and the physical ageing of the high-voltage battery.

Peaq

SKODA

